

MICRO SWITCH
 250V AC 6A RESISTIVE LOAD
 250V DC 0.5A RESISTIVE LOAD

COLOR : 10YR7.5/14
 DETECTION TORQUE : About 10.0N · cm
 REVOLUTION : 1RPM
 AMBIENT TEMPERATURE : -10 ~ +40°C

POWER SUPPLY	APPLICATION TYPE DESIGNATION
AC100V	PRL-5-WP
AC200V	PRL-5-VP

○ (Required length)

	ℓ	ℓ _o	NOTE	Q'ty
	1020~1520	0~500		
	1220~2020	0~800		
	1520~2520	0~1000		
	1720~3020	0~1300		


○ (Required length)

FLAMEPROOF TYPE CABLE GLAND G 1/2"

*Please specify the cable gland type.

CABLE GLAND TYPE	Range of acceptable cable size
SXC-16B-1	φ 10 ~ φ 12
SXC-16B-2	φ 8 ~ φ 10

○ (Required length)



APPROVAL No.: T66814
 APPLICATION RANGE: d2G4
 EXPLOSION-PROTECTED CONSTRUCTION: d
 EXPLOSION CLASS: 2
 IGNITABILITY: G4

Q'ty:

図曆 CHANGE NOTICE 承認 APPROVED 検図 CHECKED 製図 DRAWN ohno	第三角法 THIRD ANGLE PROJECTION	尺度 SCALE 1:2.5	日付 DATE Mar, 3, 2016	名称 TITLE PRL-F7ED PADDLE TYPE LEVEL SWITCH	図面番号 DRG. No. HR-91204